

# FSP Series

## FEATURES

- Mild steel construction
- 5mm thick deck plate with checkered safety tread
- Steel grid channel frame
- Painted mild steel
- Pre-corner error adjustment
- Threaded eyebolt holes for easy lifting (eyebolts included)
- Installed with:
  - \*4 high accuracy IP67 alloy steel shear beam load cells (563YH) (OIML MAA C6, Y=8,500 and NTEP 1:5000 Class III, Multiple Cell)
  - \*4 swivel mild steel feet with removable rubber base (AMF-F-1/2)
  - \*1 IP67 aluminum 4-way junction box (J04EA-16)
  - \*2 eyebolts
  - \*Level bubble



\*NTEP Approval for  
 1Klb: FSP-3X3  
 5Klb: FSP-3X3  
 FSP-4X4  
 FSP-5X5  
 10Klb: FSP-3X3  
 FSP- 4X4  
 FSP-5X5

\*Measurement Canada Approval for  
 5Klb: FSP-3X3  
 FSP-4X4  
 FSP-5X5  
 10Klb(Pending): FSP-3X3  
 FSP- 4X4  
 FSP-5X5

Part#	FSP5X5-5Klb	FSP5X5-10Klb
<b>Capacity</b>	5000lb	10000lb
<b>Division</b>	1lb	2lb
<b>Platform Size</b>	59in X 59in/ 150cm X 150cm	59in X 59in/ 150cm X 150cm
<b>Platform Material</b>	Mild Steel	Mild Steel
<b>Net Weight</b>	441lb / 200kg	441lb / 200kg
<b>Operating Temp.</b>	0 - 40°C / 32 - 104°F	0 - 40°C / 32 - 104°F

Part#	FSP3X3-1Klb	FSP3X3-5Klb	FSP3X3-10Klb	FSP4X4-5Klb	FSP4X4-10Klb
<b>Capacity</b>	1000lb	2000lb	5000lb	5000lb	10000lb
<b>Division</b>	0.2lb	0.5lb	1lb	1lb	2lb
<b>Platform Size</b>	36in X 36in/ 91.4cm X 91.4cm	36in X 36in/ 91.4cm X 91.4cm	36in X 36in/ 91.4cm X 91.4cm	48in X 48in/ 121.9cm X 121.9cm	48in X 48in/ 121.9cm X 121.9cm
<b>Platform Material</b>	Mild Steel	Mild Steel	Mild Steel	Mild Steel	Mild Steel
<b>Net Weight</b>	159lb / 72kg	159lb / 72kg	159lb / 72kg	265lb / 120kg	265lb / 120kg
<b>Operating Temp.</b>	0 - 40°C / 32 - 104°F	0 - 40°C / 32 - 104°F	0 - 40°C / 32 - 104°F	0 - 40°C / 32 - 104°F	0 - 40°C / 32 - 104°F

\*Dimensions and specifications are subject to change without notice.